



SAJ Australia Pty Ltd

Add: 17 Silicon Pl, Tullamarine VIC 3043, Australia

Website: www.saj-electric.com E-mail: info@saj-electric.com Tel: +61 3 8353 1112



R5 Series Residential Solar Inverter

R5-3K/4K/5K/6K/8K/9K/10K/15K/17K/20K-T2-AUS



-  Lightning protection
High precision leakage monitoring
-  Die-casting case cover
Beautiful & reliable
-  Low standby consumption
High efficiency, high yield
-  Remote Maintenance
Remote Configuration
-  Quiet generation
No noise pollution
-  Intelligent & Grid-friendly
Active response to grid dispatch

Technical Data

R5-3K/4K/5K/6K/8K/9K/10K/15K/17K/20K-T2-AUS

Type	R5-3K-T2-AUS	R5-4K-T2-AUS	R5-5K-T2-AUS	R5-6K-T2-AUS	R5-8K-T2-AUS	R5-9K-T2-AUS	R5-10K-T2-AUS	R5-15K-T2-AUS	R5-17K-T2-AUS	R5-20K-T2-AUS	
Input (DC)											
Max.PV Array Power [Wp] @ STC	4500	6000	7500	9000	12000	13500	15000	22500	25500	30000	
Max. DC Voltag[V]					600				1100		
MPPT Voltage range [V]					160-600				180-950		
Nominal DC Voltage[V]					480				600		
Start Voltage [V]					180				200		
Min. DC Voltage[V]					150				180		
Max. DC Input Current PV1/PV2 [A]	12.5/12.5				11/22			25/25			
Number of DC Connection Sets per MPPT	1/1				1/2			2/2			
Number of MPPT					2						
Output (AC)											
Rated AC Power[W]	3000	4000	5000	6000	8000	9000	10000	15000	17000	20000	
Max. AC Power[VA]	3300	4400	5500	6600	8800	9900	11000	16500	18700	22000	
Rated AC Current [A]	4.4	5.8	7.3	8.7	11.6	13.1	14.5	21.8	24.7	29.0	
Max. AC Current [A]	5.0	6.7	8.4	10.0	13.4	15.0	16.7	25.0	28.4	33.4	
Nominal AC voltage/ range[V]					220/380, 230/400, 240/415; 180-280/312-485						
Grid frequency/ range[Hz]					50, 60/45-55, 55-65						
Power factor[cos φ]					0.8 leading~0.8 lagging						
Total Harmonic Distortion [THDi]					<2%(at nominal power)						
Feed-in					3L+N+PE						
Efficiency											
Max. Efficiency	98.0%	98.3%	98.3%	98.3%	98.6%	98.6%	98.6%	98.7%	98.8%	98.8%	
Euro Efficiency	97.6%	98.0%	98.0%	98.0%	98.2%	98.2%	98.3%	98.4%	98.4%	98.4%	
MPPT Accuracy					> 99.5%						
Protection											
Internal Over-voltage Protection					Integrated						
DC Insulation Monitoring					Integrated						
DC Surge Protection					Integrated						
Grid Monitoring					Integrated						
AC Short Circuit Current Protection					Integrated						
AC grounding detection					Integrated						
GFCI Monitoring					Integrated						
DCI Monitoring					Integrated						
AC Surge Protection					Integrated						
Thermal Protection					Integrated						
Inverter position monitoring					AFD						
Interface											
DC Connection					MC4						
AC Connection	Plug-in connector							Terminal Block			
Human machine interface					LED+(bluetooth/Wi-Fi+APP)						
Communication port					RS232(USB joints)+RS485(RJ45 crystal joints)						
Communication Mode					Wi-Fi/GPRS/4G(Optional)						
General Data											
Topology					Transformerless						
Consumption at Night [W]					<0.6						
Consumption at Standby [W]					<10						
Operating Temperature Range					-40°C to +60°C (running in reduced load condition when the temperature is above 45°C)						
Cooling Method					Natural Convection						
Ambient Humidity					0-100% Non-condensing						
Altitude					4000m (>3000m power derating)						
Noise[dBA]					<29						
Ingress Protection					IP65						
Mounting					Rear Panel						
Dimensions[H*W*D][mm]	429*418*177							530*490*210			
Weight [kg]	19							27			
Standard Warranty [Year]					5 (standard)/10/15/20/25 (Optional)						
Applicable Standard	IEC62109-1/2, IEC61000-6-1/2/3/4, En50438, En50549, C10/C11,				IEC62116, IEC61727, Rd1699, UNE 206006, UNE 206007, CEI 0-21, AS4777.2, CQC NB/T 32004, VDE-AR-N 4105						
Manufacturing Country					China						